



## BALLAST SPECIFICATIONS

	Part No.	Description	Number of Lamps	Length	Input Watts	Ballast Factor	Starting Temp. ( F/C)	THD	Volts	Line Current (Amps)	Rapid, Program or Instant Start
T5	4425	T5 28 W	2	4	64	1	0/-18	10	120-277	0.55 - 0.23	P
	4450	T5HO 24 W	2	2	52	1	0/-18	10	120-277	0.44 - 0.19	P
	3265	T5HO 54 W	2	4	120	1	-20/-29	10	120-277	1.00 - 0.43	P
	4843	T5HO 54 W	4	4	240	1	-20/-29	10	120-277	2.00 - 0.86	P
	3613	T8 25 W	2	3	48	.91	0/-18	10	120-277	0.40 - 0.18	I
	3276	T8 25 W	2	3	48	.98	0/-18	25	347	0.14	I
	3613	T8 32 W	2	4	59	.88	0/-18	10	120-277	0.49 - 0.22	I
	3276	T8 32 W	2	4	59	.87	0/-18	20	347	0.17	I
	4766	T8 32 W	3	4	90	.97	0/-18	20	347	0.26	I
	3546	T8 25 W	4	3	89	.91	0/-18	10	120-277	0.74 - 0.32	I
T8	3125	T8 32 W	4	4	112	.85	0/-18	20	347	0.31	I
	3546	T8 32 W	4	4	112	.88	0/-18	10	120-277	0.94 - 0.41	I
	4194	T8 40 W	2	5	77	1.0	0/-18	10	120-277	0.65 - 0.28	I
	3281	T8 59 W	2	8	110	.85	32/0	20	120-277	0.95 - 0.40	I
	4854	T8HO 44 W	2	4	98	.95	-20/-29	10	120-277	0.84 - 0.36	P
	4854	T8HO 86 W	2	8	185	.95	-20/-29	10	120-277	1.57 - 0.68	P
	3792	T8HO 44 W	4	4	203	1.0	-20/-30	20	277	0.85	I
	3794	T8HO 44 W	2	4	96	1.0	-20/-30	20	277	0.48	I
	4156	T8HO 44 W	2	4	96	1.0	-20/-30	20	120	1.15	I
	4157	T8HO 44 W	4	4	203	1.0	-20/-30	20	120	1.82	I
T12	5424	T8 17 & 32 W	2	4	58	0.87	0/-18	<10	120-277	0.48 - 0.12	I
	5425	T8 17 & 32 W	4	4	112	0.87	0/-18	<10	120-277	0.94 - 0.22	I
	5470	T8 17 & 32 W	3	4	86	0.87	0/-18	<10	120-277	0.72 - 0.18	I
	6975	T8 32 W HLO	2	4	76	1.15	0/-18	20	120-277	0.65 - 0.28	I
	3260	T12 HO 60 W	2	4	134	0.89	-20/29	10	120-277	1.12-0.49	R
	1712	T12 40 W	2	4	72	.85	50/10	10	120-277	0.62-0.26	R
	3260	T12 HO 95 W	2	8	205	0.88	60/16	10	120-277	1.77-0.76	R

Other ballast types available - consult factory