

# GENERAL INDUSTRIAL LIGHTING

Commercial & Institutional Facilities • Assembly Areas • Task Lighting

Fabricated with a white powder coat finish, the 222 Series is ideal for industrial lighting needs. The 222 Series uses an optional 5 Ft. 3-wire whip which reduces installation time. Available in T8, T8HO or T5HO lamps. Lamps not included.







1 SERIES	2 LAMP TYPE	3 LAMP QUANTITY	4 LENGTH	5 VOLTAGE
222	T5HO: 54W T8: 32W T8HO: 44W	2L: (4 or 8 Ft. lamps) 3L: (4 Ft. lamps) 4L: (4 Ft. lamps T5 and T5HO only) 6L: (4 Ft. lamps) 8L: (4 Ft. lamps T5 and T5HO only)	4: 4 Ft. 8: 8 Ft.	UNV1: 120-277V (T5HO and T8 only) 120: 120V 277: 277V UNV2: 347-480V (T5HO only)
6 OPTIONS  EM: Emergency battery back up ballast SL: Slots for uplight SR: Specular Reflector NA: Narrow Angle Reflector WA: Wide Angle Reflector CM: Cable Mount (incl. 5 Ft. cable) CH: Chain Hang Kit		Notes:  T8HO is only available in a 2 lamp configuration 8 Ft. lamp fixtures only available in 2 lamp configuration 6 lamp and 8 lamp configuration only available in 8 Ft. fixtures  LAMPS SOLD SEPARATELY (Multiple voltages available, consult factory) (Consult factory for lead time on non-stock products.)		

### CERTIFICATIONS

UL 1598 CSA 22.2 No. 250.0

## **FEATURES**

Open industrial fixture Sturdy 20 gauge steel white powder coat housing Tool-less access for ease of maintenance

#### **ELECTRICAL**

Utilizes 32, 44, and 54 Watt 4 Ft. lamps.

Available in universal, 120, 277 and 347 Volts electronic ballasts (Other voltages available, consult factory)

#### **OPTIONS**

EM: Emergency battery backup ballast 120 or 277V - MUST SPECIFY SR: Specular reflector SL: Slots for up-light NA: Narrow angle reflector WA: Wide angle reflector

Mounting Kits - ordered separately

CH: Chain hanging kit CM: Cable mount kit



Standard Fixture



Standard Fixture

Fixture with Narrow Angle Reflector "NA"



Fixture with Wide Angle Reflector "WA"

# 222

# GENERAL INDUSTRIAL LIGHTING



Commercial & Institutional Facilities • Assembly Areas • Task Lighting

#### **DIMENSIONS**

