


The LENM is designed and listed for hazardous, marine, and wet locations. This product is the perfect solution for applications where corrosion resistant lighting fixtures are required.



1 SERIES	2 LENGTH *	3 LAMP/MODULE QTY	4 LED TYPE	5 VOLTAGE	6 OPTIONS
LENM	2: 2 Ft. 4: 4 Ft. *Nominal	2: (2) LED Tube Lamps <or> (2) LED Modules 3: (3) LED Tube Lamps	LEDT8: LED Tube Lamp LED*: LED Module *Qty 2 only	V1: 120-277V (50/60Hz)	EM*: Emergency Backup (90 min.) UL924 P: Polycarbonate Frosted Lens SS: Stainless steel captive latches *LED only. Not available with LEDT8.

CERTIFICATIONS

UL844 / CSA-C22.2 No.137 (Hazardous)
 CI D2, Grps A, B, C, D
 CII D2, Grps F, G
 T-Code: T4
 UL1598 / CSA-C22.2 No.250 (Wet/Damp)
 UL1598A (Marine Outside)
 CRI Ra>80 (Both LED Types)
 40°C Ambient
 EM Option: 0°C to 40°C Ambient

PERFORMANCE

Electrical Performance Table				
LED Type	Length	Wattage (W)	CCT	Lumen
LED Tube Lamp (#LEDT8)	2Ft. - 2 Row	14	5,000K	1,830
	2Ft. - 3 Row	21		2,690
	4Ft. - 2 Row	30		3,650
	4Ft. - 3 Row	45		5,380
LED Module (#LED)	2Ft.	34		4,530
	4Ft.	67		9,050

CONSTRUCTION

Housing - Non-metallic glass reinforced polyester
 Frosted acrylic (standard)
 Acetal lens latches
 Stainless steel mounting brackets
 1/2" NPT hubs each end (standard)
 Weights: 2 Ft.= 10lbs. 4 Ft.= 20lbs.

ELECTRICAL

120-277VAC (50/60Hz)

FEATURES

5 Year Warranty
 Field replaceable LED boards and drivers
 (if applicable)

DIMENSIONS - (NOMINAL)

